



### DESCRIPTION

24V DC 75W LED flexible strip for dry locations  
 CRI 90+ Perfect light consistency with wide beam angle  
 Easy to install and low maintenance  
 Versatile accessories for installation  
 High brightness 4.5W per foot with 7 LEDs per inch

### APPLICATIONS

Cove lighting  
 Path and contour marking  
 DIY lights for home undercabinet and valance use  
 Decorative lights for holiday, event, show, exhibition

Project:

Location:

Cat # :




Qty:

Notes:

SPECIFICATION (tolerance +/- 10%)				
Applications	Undercabinet, Cove, Valance, Decorative			
Color Temperature (K)	2700	3000	4000	5000
Power W/ft	4.5			
Efficiency lm/W	95	100	105	110
Lumen lm/ft	430	460	480	500
Length per roll	16.4 ft / 5 meters			
Maximum Length	16.4 ft / 5 meters			
Power per Max Length	75W			
Lumen per Max Length	7,125	7,500	7,875	8,250
Beam Angle	120°			
CRI	90 +			
Input	24V DC			
Dimmable	Yes			
LED Operation Type	Constant Voltage			
IP Grade	IP 20			
Approved Location	Indoor / Dry Location			
Ambient Temperature	-4°F (-20°C) to +104°F (+40°C)			
LED source	SMD 2216			
Cutable Increment	1"			
LEDs per Increment	7			
Adhesive Tape Type	3M 300SE			
Projected Life	70% Light Output at 20,000 Hours			
Certification	cETLus			
Warranty	3 Year			

LED Strip

Aluminum Channel (Optional)



24V DC

7 LEDs per inch

### ACCESSORIES

Sold Separately



24V 96W cULus Class 2 Driver  
 120V Input cat # **LBL-DC24V96W**  
 Triac and 0-10V Dimmable



Aluminum Channel With Diffused Cover  
 3.3' cat # XC610



Strip Connector No Wires cat # LSC-0



Single Connector with 6" cat # LSC-1



Two Connectors with 6" Between cat # LSC-2

Note: Connectors do not fit inside the channel

### ORDERING GUIDE

2700K	DDC-H060-24V-NA-5M-27K
3000K	DDC-H060-24V-NA-5M-30K
4000K	DDC-H060-24V-NA-5M-40K
5000K	DDC-H060-24V-NA-5M-50K