



Kinetic Doorbell Set with Plug-In Receiver



No Wires & Batteries Required

DESCRIPTION

Wireless Kinetic Doorbell Set that employs micro-energy acquisition technology to provide battery-free installation

FEATURES & BENEFITS

Wireless & Batteryless

Waterproof Transmitter for Outdoor Installation


Pair multiple units together

Choose from 38 melodies with 4 levels of volume,

plus a flashing light

True Plug & Play Installation & Operation:

Mount the Transmitter, Plug the Receiver & Ring the Bell



ORDERING GUIDE

Set or Transmitter and Plug-in Receiver LBL-KDB-1
Transmitter Only LBL-KDB-T1
Plug-in Receiver Only LBL-KDB-R1

Optional:

Hard Wired Doorbell Receiver <u>LBL-KDB-R2</u>

Kinetic Door Sensor LBL-KDS



| Project: | | | |
|-----------|--|--|--|
| Location: | | | |
| Qty: | | | |
| Notes: | | | |

| | SPECIFICATION | | |
|-------------------------|---|--|--|
| Applications | Homes, Multi-Family, Workshops, etc. | | |
| Receiver Input Voltage | 100 - 240V AC | | |
| Energy Used by Receiver | idle 0.1 W, while ringing 0.6 W | | |
| Volume Levels | 4 | | |
| Ringtones | 38 | | |
| Daining Consolt. | up to 100 receivers to 1 transmitter | | |
| Pairing Capacity | up to 10 transmitters to 1 receiver | | |
| Operation Range | 100 feet | | |
| Frequency | 433 MHz | | |
| On anating Tanananatura | Receiver: -10°C to + 55°C (14°F to 130°F) | | |
| Operating Temperature | Transmitter: -40°C to + 55°C (-40°F to 130°F) | | |
| Approved Location | Receiver: Indoor only | | |
| Approved Location | Transmitter: Outdoor IP67 | | |
| Certifications | c ETL us, FCC | | |
| Warranty | 2 Year | | |

Pairing:

The Transmitter and Receiver in your package are already paired.

To pair more than one follow the steps below:







- 1. Press the Ringtone Selection Key for 3 seconds and release when the indicatior light starts blinking
- 2. Press the Transmitter once. The indicator light on the Receiver will turn off and the pairing is complete

Deleting Pair:

The pairing will be deleted by pressing the Ringtone Selection Key for 10 seconds until the indicator light stops blinking and is constantly on

Silent Mode:

To activate Silent Mode, press the Ringtone Selection Key for 8 seconds and release when the indicator light stops blinking and is constantly on To deactivate Silent Mode: repeat the above steps

Note: Could be used in combination with the Hard Wired Receiver & Kinetic Door Sensor (will sound when door opens or closes)

| Lotus LED Lights USA | | | | |
|--|--|--|--|--|
| 250 H Street # 301, Blaine WA 98230 tel 360-200-5500 | | | | |
| Hainesport NJ, Naples FL, Vancouver WA | | | | |