



Type IC, Air-Tight, Wet & Plenum

DESCRIPTION

6" Square Recessed LED With Built-In Driver Commercial Grade Quality With Architectural Design


FEATURES & BENEFITS

2 1/4" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required CRI 90+ for True Color Rendering Fast & Easy To Install - Save On Labor Connection Box Included - No Junction Box Needed Armored Cable - Open Plenum Rated

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2 1/4"

DIMENSIONS: ID 6" OD 7" Cut Out 6" to 6 1/2"



ORDERING GUIDE Example: LL6SRG - 30K - WH

	CCT	Trim Finish	
LL6SRG	-	-	
2700K	27K	WH	White
3000K	30K	ВК	Black
4100K	41K		

LL6SRG

6" Square Regressed 1st Gen Plenum LED 18W

Project:		
Location:		
Cat #:	Qty:	
Notes:		

SPECIFICATION				
Applications	Recessed Ceiling Mount			
Energy Used	18 W			
Color Temperature	2700 3000 4100			
Light Output	1000 1020 1050			
Halogen Equivalent	100 W			
Beam Angle	90°			
CRI	90 +			
Input Voltage	120V AC 50/60 Hz			
Dimming	TRIAC Dimmers 5%-100%			
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG			
Power Factor	0.98			
Approved Location	Insulated Ceilings, Open Plenum, Wet			
IP Rating	IP 54			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 50,000 Hours			
Certification	cULus			
Warranty	10 Year Residential / 5 Year Commercial			

AVAILABLE TRIMS





White

Black

ACCESSORIES

Sold Separately



26" Flat Rough-In Plates - cat # RIP6



13" Flat Rough-In Plate - cat # MP6-2



Flanged Plate with Hanger Bars - cat # FRP6

COMPLIANCE





Type IC Air-Tight Open Plenum