



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 67.46 lm/W			
MODEL		I _{max} (cd)	1898	S/MH (C0/180)	0.54
NOMINAL POWER (W)	12	LOR (%)	100.0	S/MH (C90/270)	0.52
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	791.22	<input type="checkbox"/> UP, DN (C0-180)	0.0, 52.4
NOMINAL FLUX (lm)	791.225	CIE CLASS	DIRECT	<input type="checkbox"/> UP, DN (C180-360)	0.0, 47.6
LAMPS INSIDE	1	<input type="checkbox"/> up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	12	<input type="checkbox"/> down (%)	100.0	CIBSE SHR MAX	0.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity: 65.0%
 Test Distance: 3.080m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	1478	1510	1535	1524	1470	1425	1420	1444	0- 10	160.3	160.3	20.3,20.3
20	703.4	734.5	752.4	742.7	687.3	641.7	636.4	661.9	10- 20	293.6	453.8	57.4,57.4
30	255.1	282.0	294.6	272.6	252.8	244.7	239.3	246.1	20- 30	198.2	652.0	82.4,82.4
40	69.44	75.76	82.41	77.83	68.20	63.56	62.54	66.17	30- 40	94.98	747.0	94.4,94.4
50	18.47	20.30	20.77	19.57	17.55	16.12	15.80	16.82	40- 50	30.06	777.1	98.2,98.2
60	5.575	5.813	5.799	5.566	5.203	5.077	5.132	5.315	50- 60	8.550	785.6	99.3,99.3
70	3.085	3.064	2.880	2.853	2.813	2.676	2.589	2.873	60- 70	3.970	789.6	99.8,99.8
80	0.3791	0.3457	0.2223	0.2865	0.3849	0.2091	0.1280	0.2046	70- 80	1.553	791.2	100,100
90	0.0281	0.0163	0.0140	0.0050	0.0288	0.0170	0.0134	0.0071	80- 90	0.0698	791.2	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	5	3
80	20	12
75	66	44
70	82	76
65	89	87
60	101	104
55	138	151
50	261	290
45	481	530


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.09	1.07	1.09	1.07	1.06	1.05	1.04	1.02	1.02	1.01	.99	.98	.97	.97	.95
2.0	1.05	1.01	.98	1.03	.90	.97	1.00	.97	.95	.97	.95	.93	.94	.93	.91	.90
3.0	.99	.95	.91	.98	.94	.90	.95	.92	.89	.93	.90	.88	.90	.88	.86	.85
4.0	.94	.89	.85	.93	.88	.85	.90	.87	.84	.89	.85	.83	.87	.84	.82	.80
5.0	.89	.84	.80	.88	.83	.80	.86	.82	.79	.85	.81	.78	.83	.80	.78	.76
6.0	.84	.79	.76	.84	.79	.75	.82	.78	.75	.81	.77	.74	.80	.76	.74	.73
7.0	.81	.75	.72	.80	.75	.71	.79	.74	.71	.78	.74	.71	.77	.73	.70	.69
8.0	.77	.72	.68	.76	.71	.68	.75	.71	.68	.74	.70	.67	.73	.70	.67	.66
9.0	.74	.68	.65	.73	.68	.65	.72	.68	.65	.71	.67	.65	.71	.67	.64	.63
10.0	.71	.66	.62	.70	.65	.62	.69	.65	.62	.69	.65	.62	.68	.64	.62	.61



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Wall Exitance Coefficients (WEC)			
0.0						
1.0	.161 .092 .029	.155 .088 .028	.142 .082 .026	.131 .075 .024	.120 .070 .022	
2.0	.153 .084 .026	.147 .081 .025	.137 .076 .024	.127 .071 .022	.118 .067 .021	
3.0	.144 .077 .023	.140 .075 .023	.131 .071 .022	.123 .067 .021	.115 .064 .020	
4.0	.137 .071 .021	.133 .069 .021	.125 .066 .020	.118 .063 .019	.112 .061 .018	
5.0	.130 .066 .019	.126 .065 .019	.120 .062 .018	.114 .060 .018	.108 .058 .017	
6.0	.123 .062 .018	.120 .061 .018	.115 .059 .017	.109 .057 .017	.104 .055 .016	
7.0	.118 .058 .017	.115 .057 .016	.110 .056 .016	.105 .054 .016	.101 .052 .015	
8.0	.113 .055 .015	.110 .054 .015	.106 .053 .015	.102 .051 .015	.098 .050 .015	
9.0	.108 .052 .015	.106 .051 .014	.102 .050 .014	.098 .049 .014	.094 .048 .014	
10.0	.103 .050 .014	.101 .049 .014	.098 .048 .014	.095 .047 .013	.091 .046 .013	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Ceiling Cavity Exitance Coefficients (CCEC)			
0.0	.190 .190 .190	.163 .163 .163	.111 .111 .111	.064 .064 .064	.020 .020 .020	
1.0	.170 .157 .146	.145 .135 .126	.100 .093 .087	.057 .054 .051	.018 .017 .016	
2.0	.154 .133 .115	.132 .114 .099	.090 .079 .069	.052 .046 .041	.017 .015 .013	
3.0	.140 .113 .092	.120 .098 .080	.083 .068 .056	.048 .040 .033	.015 .013 .011	
4.0	.129 .098 .075	.111 .085 .065	.076 .059 .046	.044 .035 .027	.014 .011 .009	
5.0	.120 .087 .062	.103 .075 .054	.071 .052 .038	.041 .031 .023	.013 .010 .007	
6.0	.112 .077 .052	.096 .067 .045	.066 .047 .032	.038 .027 .019	.012 .009 .006	
7.0	.105 .069 .044	.090 .060 .039	.062 .042 .027	.036 .025 .016	.012 .008 .005	
8.0	.099 .063 .038	.085 .054 .033	.059 .038 .024	.034 .023 .014	.011 .007 .005	
9.0	.093 .057 .033	.081 .050 .029	.056 .035 .020	.033 .021 .012	.011 .007 .004	
10.0	.089 .053 .029	.077 .046 .025	.053 .032 .018	.031 .019 .011	.010 .006 .004	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm										
NAME: AD-35-S12W-5CCT-WH-REY					TYPE:			WEIGHT:		
SPEC.:2700K 90					DIM.:			SERIAL No.:		
MFR.:					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	5.0	5.8	5.2	6.0	6.1	5.6	6.4	5.8	6.6	6.7
3H	4.9	5.7	5.2	5.9	6.1	5.5	6.3	5.8	6.5	6.7
4H	4.9	5.6	5.2	5.9	6.1	5.4	6.2	5.7	6.4	6.6
6H	4.8	5.5	5.1	5.8	6.0	5.4	6.0	5.7	6.3	6.5
8H	4.8	5.5	5.1	5.7	6.0	5.3	6.0	5.6	6.2	6.5
12H	4.8	5.4	5.1	5.6	5.9	5.3	5.9	5.6	6.2	6.4
4H 2H	4.8	5.5	5.1	5.8	6.0	5.4	6.1	5.7	6.3	6.5
3H	4.8	5.4	5.1	5.7	6.0	5.3	6.0	5.6	6.2	6.5
4H	4.8	5.4	5.1	5.7	6.0	5.3	5.8	5.6	6.1	6.4
6H	4.7	5.2	5.1	5.5	5.9	5.2	5.7	5.6	6.0	6.4
8H	4.7	5.1	5.0	5.5	5.8	5.1	5.6	5.5	6.0	6.3
12H	4.6	5.0	5.0	5.4	5.8	5.1	5.5	5.5	5.9	6.3
8H 4H	4.7	5.1	5.1	5.5	5.8	5.2	5.6	5.5	6.0	6.3
6H	4.6	5.0	5.0	5.4	5.8	5.1	5.4	5.5	5.8	6.2
8H	4.5	4.9	5.0	5.3	5.7	5.0	5.3	5.4	5.8	6.2
12H	4.5	4.8	4.9	5.2	5.7	4.9	5.2	5.4	5.7	6.1
12H 4H	4.6	5.0	5.0	5.4	5.8	5.1	5.5	5.5	5.9	6.3
6H	4.5	4.9	5.0	5.3	5.7	5.0	5.3	5.4	5.8	6.2
8H	4.5	4.8	4.9	5.2	5.7	4.9	5.2	5.4	5.7	6.1
Variations with the observer position at spacings:										
S = 1.0H	+ 2.5 / - 5.7					+ 3.0 / - 6.6				
1.5H	+ 4.1 / - 5.1					+ 4.8 / - 5.8				
2.0H	+ 4.6 / - 3.4					+ 5.1 / - 4.0				

CIE Pub.117, 791.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.8)
 Area: 0.111111 m2

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	88	82	78	88	82	78	87	81	78	74
0.80	95	90	86	95	89	86	94	89	86	82
1.00	100	94	91	99	94	90	97	94	90	86
1.25	104	99	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	92
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

AAI Figure

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	84
L_0~180 (75) av	62
L_0~180 (85) av	6
L_90~270 (65) av	84
L_90~270 (75) av	36
L_90~270 (85) av	2
L_45 (65) av	84
L_45 (75) av	51
L_45 (85) av	2

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.05V I:0.1267A P:11.729W PF:0.9237 Freq:59.98Hz Lamp Flux:791.225x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:2700K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896	1896			
5	1787	1800	1805	1813	1816	1815	1803	1793	1780	1764	1759	1750	1752	1755	1767	1774			
10	1478	1497	1510	1527	1535	1539	1524	1502	1470	1440	1425	1413	1420	1424	1444	1459			
15	1084	1107	1114	1132	1139	1148	1133	1106	1068	1029	1012	1001	1007	1012	1041	1060			
20	703	727	734	749	752	759	743	717	687	656	642	630	636	641	662	678			
25	423	440	450	465	467	469	456	439	420	401	391	378	381	385	395	404			
30	255	268	282	294	295	290	273	263	253	247	245	238	239	242	246	248			
35	154	163	169	180	180	174	159	149	140	134	129	127	132	136	145	146			
40	69.4	74.6	75.8	80.0	82.4	82.0	77.8	71.4	68.2	65.2	63.6	62.0	62.5	63.0	66.2	66.2			
45	37.4	39.9	40.7	41.2	41.7	41.8	40.1	37.7	36.0	34.7	34.3	33.3	33.3	33.8	35.1	35.5			
50	18.5	20.0	20.3	20.9	20.8	20.8	19.6	18.6	17.6	16.3	16.1	15.8	15.8	15.9	16.8	17.4			
55	8.73	9.26	9.40	9.58	9.65	9.35	8.95	8.53	8.15	7.83	7.72	7.67	7.71	7.76	8.08	8.34			
60	5.58	5.75	5.81	5.83	5.80	5.71	5.57	5.37	5.20	5.08	5.08	5.09	5.13	5.19	5.31	5.46			
65	4.12	4.19	4.19	4.16	4.08	4.03	3.98	3.88	3.78	3.71	3.72	3.73	3.77	3.84	3.96	4.04			
70	3.09	3.13	3.06	3.00	2.88	2.86	2.85	2.89	2.81	2.75	2.68	2.61	2.59	2.71	2.87	3.02			
75	1.89	2.00	1.76	1.43	1.26	1.32	1.56	1.74	1.69	1.54	1.21	0.88	0.81	0.89	1.30	1.67			
80	0.38	0.51	0.35	0.24	0.22	0.22	0.29	0.34	0.38	0.36	0.21	0.14	0.13	0.14	0.20	0.30			
85	0.04	0.06	0.03	0.03	0.03	0.02	0.02	0.02	0.07	0.05	0.02	0.02	0.02	0.01	0.01	0.02			
90	0.03	0.02	0.02	0.02	0.01	0.01	0.01	0.00	0.03	0.02	0.02	0.01	0.01	0.01	0.01	0.01			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-12
 □ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: