



**LUMINAIRE PHOTOMETRIC TEST REPORT**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 79.73 lm/W			
MODEL		I <sub>max</sub> (cd)	2199	S/MH (C0/180)	0.54
NOMINAL POWER (W)	12	LOR (%)	100.0	S/MH (C90/270)	0.52
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	924.23	<input type="checkbox"/> UP, DN (C0-180)	0.0, 52.6
NOMINAL FLUX (lm)	924.229	CIE CLASS	DIRECT	<input type="checkbox"/> UP, DN (C180-360)	0.0, 47.4
LAMPS INSIDE	1	<input type="checkbox"/> up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	12	<input type="checkbox"/> down (%)	100.0	CIBSE SHR MAX	0.55



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity: 65.0%  
 Test Distance: 3.080m [K=1.0000]  
 Remarks:

**ZONAL FLUX DIAGRAM**

ZONAL FLUX DIAGRAM:


°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	1733	1759	1780	1759	1696	1643	1643	1683	0- 10	185.7	185.7	20.1,20.1
20	840.8	864.4	875.3	863.9	794.9	740.3	735.1	781.2	10- 20	341.6	527.4	57.1,57.1
30	310.6	332.7	343.3	321.7	298.9	281.8	277.5	292.8	20- 30	232.6	760.0	82.2,82.2
40	86.59	90.60	97.05	91.56	80.14	72.88	72.57	78.05	30- 40	111.9	871.9	94.3,94.3
50	22.66	24.30	24.64	22.93	20.44	18.96	18.53	20.25	40- 50	35.48	907.4	98.2,98.2
60	6.771	7.018	6.954	6.632	6.155	6.018	6.094	6.371	50- 60	10.19	917.6	99.3,99.3
70	3.713	3.651	3.395	3.377	3.312	3.153	3.050	3.424	60- 70	4.734	922.3	99.8,99.8
80	0.4732	0.4151	0.2583	0.3361	0.4307	0.2386	0.1525	0.2457	70- 80	1.836	924.1	100,100
90	0.0337	0.0320	0.0284	0.0080	0.0290	0.0184	0.0194	0.0107	80- 90	0.0852	924.2	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

□ Range: 0 - 90DEG  
 □ Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**LUMINANCE LIMITATION CURVES**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	6	4
80	25	13
75	81	51
70	98	89
65	106	103
60	122	125
55	168	178
50	317	345
45	584	626


C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.09	1.07	1.09	1.07	1.06	1.05	1.04	1.02	1.02	1.00	.99	.98	.97	.96	.95
2.0	1.05	1.01	.98	1.03	.90	.97	1.00	.97	.95	.97	.95	.93	.94	.93	.91	.90
3.0	.99	.94	.91	.98	.93	.90	.95	.92	.89	.93	.90	.87	.90	.88	.86	.85
4.0	.94	.89	.85	.92	.88	.84	.90	.87	.83	.88	.85	.83	.87	.84	.82	.80
5.0	.89	.84	.80	.88	.83	.79	.86	.82	.79	.85	.81	.78	.83	.80	.77	.76
6.0	.84	.79	.75	.84	.79	.75	.82	.78	.75	.81	.77	.74	.80	.76	.74	.72
7.0	.80	.75	.72	.80	.75	.71	.79	.74	.71	.77	.74	.71	.76	.73	.70	.69
8.0	.77	.72	.68	.76	.71	.68	.75	.71	.68	.74	.70	.67	.73	.70	.67	.66
9.0	.73	.68	.65	.73	.68	.65	.72	.68	.65	.71	.67	.64	.71	.67	.64	.63
10.0	.70	.65	.62	.70	.65	.62	.69	.65	.62	.69	.65	.62	.68	.64	.62	.60



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

WEC AND CCEC

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Wall Exitance Coefficients (WEC)			
0.0						
1.0	.162 .092 .029	.155 .088 .028	.142 .082 .026	.131 .076 .024	.120 .070 .022	
2.0	.153 .084 .026	.148 .081 .025	.137 .076 .024	.128 .072 .022	.119 .067 .021	
3.0	.145 .077 .023	.140 .075 .023	.131 .071 .022	.123 .067 .021	.115 .064 .020	
4.0	.137 .071 .021	.133 .070 .021	.126 .067 .020	.119 .064 .019	.112 .061 .019	
5.0	.130 .066 .019	.127 .065 .019	.120 .063 .018	.114 .060 .018	.108 .058 .017	
6.0	.124 .062 .018	.121 .061 .018	.115 .059 .017	.110 .057 .017	.105 .055 .016	
7.0	.118 .058 .017	.115 .058 .016	.110 .056 .016	.106 .054 .016	.101 .053 .015	
8.0	.113 .055 .015	.110 .054 .015	.106 .053 .015	.102 .052 .015	.098 .050 .015	
9.0	.108 .052 .015	.106 .052 .014	.102 .050 .014	.098 .049 .014	.095 .048 .014	
10.0	.104 .050 .014	.102 .049 .014	.098 .048 .014	.095 .047 .013	.092 .046 .013	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Ceiling Cavity Exitance Coefficients (CCEC)			
0.0	.190 .190 .190	.163 .163 .163	.111 .111 .111	.064 .064 .064	.020 .020 .020	
1.0	.170 .157 .146	.146 .135 .126	.100 .093 .087	.057 .054 .051	.018 .017 .016	
2.0	.154 .133 .115	.132 .114 .099	.090 .079 .069	.052 .046 .041	.017 .015 .013	
3.0	.140 .113 .092	.120 .098 .080	.083 .068 .056	.048 .040 .033	.015 .013 .011	
4.0	.129 .098 .075	.111 .085 .065	.076 .059 .046	.044 .035 .027	.014 .011 .009	
5.0	.120 .087 .062	.103 .075 .054	.071 .052 .038	.041 .031 .023	.013 .010 .007	
6.0	.112 .077 .052	.096 .067 .045	.066 .047 .032	.038 .027 .019	.012 .009 .006	
7.0	.105 .069 .044	.090 .060 .039	.062 .042 .027	.036 .025 .016	.012 .008 .005	
8.0	.099 .063 .038	.085 .054 .033	.059 .038 .024	.034 .023 .014	.011 .007 .005	
9.0	.094 .057 .033	.081 .050 .029	.056 .035 .020	.033 .021 .012	.011 .007 .004	
10.0	.089 .053 .029	.077 .046 .025	.053 .032 .018	.031 .019 .011	.010 .006 .004	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**UGR(Unified Glare Rating) Table**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	5.2	6.0	5.4	6.2	6.3	5.6	6.5	5.8	6.6	6.8
3H	5.1	5.9	5.4	6.1	6.3	5.6	6.3	5.8	6.5	6.7
4H	5.1	5.8	5.4	6.0	6.3	5.5	6.2	5.8	6.4	6.7
6H	5.0	5.7	5.3	6.0	6.2	5.4	6.1	5.7	6.3	6.6
8H	5.0	5.6	5.3	5.9	6.2	5.4	6.0	5.7	6.3	6.5
12H	4.9	5.6	5.3	5.8	6.1	5.3	6.0	5.6	6.2	6.5
4H 2H	5.0	5.7	5.3	6.0	6.2	5.4	6.2	5.7	6.4	6.6
3H	5.0	5.6	5.3	5.9	6.2	5.4	6.0	5.7	6.3	6.6
4H	5.0	5.5	5.3	5.8	6.1	5.3	5.9	5.7	6.2	6.5
6H	4.9	5.4	5.3	5.7	6.1	5.2	5.7	5.6	6.1	6.4
8H	4.9	5.3	5.2	5.7	6.0	5.2	5.7	5.6	6.0	6.4
12H	4.8	5.2	5.2	5.6	6.0	5.1	5.6	5.5	5.9	6.3
8H 4H	4.9	5.3	5.2	5.7	6.0	5.2	5.7	5.6	6.0	6.4
6H	4.8	5.2	5.2	5.6	6.0	5.1	5.5	5.5	5.9	6.3
8H	4.7	5.1	5.2	5.5	5.9	5.1	5.4	5.5	5.8	6.3
12H	4.7	5.0	5.1	5.4	5.9	5.0	5.3	5.5	5.7	6.2
12H 4H	4.8	5.2	5.2	5.6	6.0	5.2	5.6	5.6	6.0	6.3
6H	4.7	5.1	5.2	5.5	5.9	5.1	5.4	5.5	5.8	6.3
8H	4.7	5.0	5.1	5.4	5.9	5.0	5.3	5.5	5.7	6.2
Variations with the observer position at spacings:										
S = 1.0H	+ 2.7 / - 5.7					+ 3.0 / - 6.5				
1.5H	+ 4.3 / - 5.0					+ 4.7 / - 5.6				
2.0H	+ 4.6 / - 3.4					+ 5.0 / - 4.0				

CIE Pub.117, 924.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.3)  
 Area: 0.111111 m2

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**UTILIZATION FACTORS TABLE**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	88	82	78	87	82	78	87	81	78	74
0.80	95	90	86	95	89	86	94	89	85	82
1.00	100	94	91	99	94	90	97	94	90	86
1.25	104	99	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	92
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:



**AAI Figure**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**ISOLUX DIAGRAM**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**LED Avg.L Report**

Test:U:120.04V I:0.1257A P:11.592W PF:0.9255 Freq:59.98Hz Lamp Flux:924.229x1 lm		
NAME: AD-35-S12W-5CCT-WH-REY	TYPE:	WEIGHT:
SPEC.:4000K 90	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	101
L_0~180 (75) av	74
L_0~180 (85) av	7
L_90~270 (65) av	99
L_90~270 (75) av	42
L_90~270 (85) av	3
L_45 (65) av	101
L_45 (75) av	60
L_45 (85) av	3

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**Planar Illuminance Curve**



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2021-08-12

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity: 65.0%  
 Test Distance: 3.080m [K=1.0000]  
 Remarks:

