



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	DL254-8-35W-M-A5C5-HO	Imax (cd)	954.2	S/MH (C0/180)	1.15
NOMINAL POWER (W)	22	LOR (%)	100.0	S/MH (C90/270)	1.15
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	1883.7	<input type="checkbox"/> UP, DN (C0-180)	0.0,50.3
NOMINAL FLUX (lm)	1883.7	CIE CLASS	DIRECT	<input type="checkbox"/> UP, DN (C180-360)	0.0,49.7
LAMPS INSIDE	1	<input type="checkbox"/> up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	<input type="checkbox"/> down (%)	100.0	CIBSE SHR MAX	1.25



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators: DAMIN
 Test Date: 2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity: 65.0%
 Test Distance: 9.680m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum,lamp
10	926.5	927.2	929.6	930.4	928.9	927.3	924.4	922.4	0- 10	89.73	89.73	4.76,4.76
20	847.5	850.1	854.7	857.4	854.2	851.9	847.1	841.8	10- 20	251.9	341.6	18.1,18.1
30	728.8	731.7	737.6	742.3	736.6	734.8	727.1	722.2	20- 30	366.1	707.7	37.6,37.6
40	567.9	571.8	581.1	587.6	581.1	577.4	569.7	563.6	30- 40	411.6	1119	59.4,59.4
50	364.5	371.5	379.6	387.3	384.5	378.4	370.4	363.5	40- 50	366.6	1486	78.9,78.9
60	173.6	177.1	182.3	186.7	187.9	184.7	176.5	169.4	50- 60	244.8	1731	91.9,91.9
70	51.67	51.78	53.34	55.12	55.63	55.94	53.18	51.53	60- 70	105.9	1837	97.5,97.5
80	21.17	21.41	21.92	22.59	22.54	22.68	22.03	21.98	70- 80	36.58	1873	99.4,99.4
90	0.5310	0.5310	0.4982	0.5179	0.8981	0.8981	0.8981	0.9112	80- 90	10.56	1884	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1314.1 lm

%lum = 69.8%

%lamp = 69.8%

Conical surface Flux(130deg): 1798.3 lm

%lum = 95.5%


%lamp = 95.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3275	2948
80	3810	3945
75	3984	4085
70	4721	4874
65	7341	7637
60	10851	11396
55	14358	15098
50	17722	18454
45	20688	21339


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz		
UTHdi:0.00% ITHdi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.07	1.04	1.01	1.05	1.02	.99	1.01	.98	.96	.97	.95	.93	.93	.92	.90	.88
2.0	.96	.90	.86	.94	.89	.85	.91	.86	.83	.88	.84	.81	.85	.82	.79	.77
3.0	.86	.79	.74	.85	.78	.73	.82	.76	.72	.79	.75	.71	.77	.73	.70	.68
4.0	.78	.70	.64	.76	.69	.64	.74	.68	.63	.72	.66	.62	.70	.65	.61	.59
5.0	.70	.62	.57	.69	.62	.56	.67	.61	.56	.65	.60	.55	.64	.59	.55	.53
6.0	.64	.56	.50	.63	.56	.50	.61	.55	.50	.60	.54	.49	.58	.53	.49	.47
7.0	.59	.51	.45	.58	.50	.45	.56	.50	.45	.55	.49	.44	.54	.48	.44	.42
8.0	.54	.46	.41	.53	.46	.41	.52	.45	.40	.51	.45	.40	.50	.44	.40	.38
9.0	.50	.42	.37	.49	.42	.37	.48	.41	.37	.47	.41	.37	.46	.40	.36	.35
10.0	.46	.39	.34	.46	.38	.34	.45	.38	.34	.44	.38	.33	.43	.37	.33	.32



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Wall Exitance Coefficients(WEC)			
0.0						
1.0	.246 .140 .044	.239 .136 .043	.226 .130 .041	.214 .123 .040	.203 .118 .038	
2.0	.238 .131 .040	.232 .128 .039	.221 .123 .038	.211 .118 .037	.201 .114 .036	
3.0	.226 .121 .036	.221 .118 .036	.211 .115 .035	.202 .111 .034	.194 .107 .033	
4.0	.214 .111 .033	.209 .109 .032	.200 .106 .032	.192 .103 .031	.185 .100 .031	
5.0	.201 .103 .030	.197 .101 .029	.189 .099 .029	.182 .096 .029	.176 .094 .028	
6.0	.189 .095 .027	.186 .094 .027	.179 .092 .027	.173 .090 .026	.167 .088 .026	
7.0	.179 .088 .025	.175 .087 .025	.169 .086 .025	.163 .084 .024	.158 .082 .024	
8.0	.169 .082 .023	.166 .082 .023	.160 .080 .023	.155 .079 .023	.150 .077 .022	
9.0	.159 .077 .022	.157 .076 .021	.152 .075 .021	.147 .074 .021	.143 .073 .021	
10.0	.151 .072 .020	.149 .072 .020	.144 .071 .020	.140 .070 .020	.136 .068 .020	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Ceiling Cavity Exitance Coefficients(CCEC)			
0.0	.190 .190 .190	.163 .163 .163	.111 .111 .111	.064 .064 .064	.020 .020 .020	
1.0	.176 .157 .139	.150 .134 .120	.103 .093 .083	.059 .054 .048	.019 .017 .016	
2.0	.165 .132 .104	.141 .114 .090	.097 .079 .063	.056 .046 .037	.018 .015 .012	
3.0	.156 .114 .080	.134 .098 .070	.092 .068 .049	.053 .040 .029	.017 .013 .009	
4.0	.148 .100 .064	.127 .087 .055	.087 .060 .039	.051 .035 .023	.016 .012 .008	
5.0	.141 .089 .052	.121 .077 .045	.083 .054 .032	.048 .032 .019	.016 .010 .006	
6.0	.134 .081 .043	.115 .070 .037	.079 .049 .026	.046 .029 .016	.015 .009 .005	
7.0	.128 .074 .036	.110 .064 .031	.076 .045 .022	.044 .026 .013	.014 .009 .004	
8.0	.122 .068 .031	.105 .059 .027	.073 .041 .019	.042 .024 .011	.014 .008 .004	
9.0	.116 .063 .027	.100 .055 .023	.069 .038 .017	.040 .023 .010	.013 .007 .003	
10.0	.111 .059 .024	.096 .051 .021	.067 .036 .015	.039 .021 .009	.013 .007 .003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.5	22.8	21.8	23.0	23.2	21.6	23.0	21.9	23.2	23.4
3H	21.7	22.9	22.0	23.1	23.3	21.8	23.0	22.1	23.3	23.5
4H	21.7	22.8	22.0	23.1	23.3	21.8	23.0	22.2	23.2	23.5
6H	21.7	22.8	22.0	23.0	23.3	21.9	22.9	22.2	23.2	23.5
8H	21.7	22.7	22.0	23.0	23.3	21.9	22.9	22.2	23.2	23.5
12H	21.7	22.7	22.0	23.0	23.3	21.8	22.8	22.2	23.1	23.4
4H 2H	21.6	22.8	21.9	23.0	23.3	21.8	22.9	22.1	23.1	23.4
3H	21.9	22.9	22.2	23.1	23.4	22.0	23.0	22.3	23.3	23.6
4H	21.9	22.8	22.3	23.2	23.5	22.1	23.0	22.4	23.3	23.6
6H	22.0	22.8	22.4	23.2	23.5	22.2	23.0	22.6	23.3	23.7
8H	22.1	22.8	22.5	23.1	23.5	22.2	22.9	22.6	23.3	23.7
12H	22.1	22.7	22.5	23.1	23.5	22.2	22.9	22.6	23.2	23.6
8H 4H	21.9	22.6	22.3	23.0	23.4	22.0	22.8	22.4	23.1	23.5
6H	22.1	22.7	22.5	23.1	23.5	22.2	22.8	22.6	23.2	23.6
8H	22.1	22.7	22.6	23.1	23.5	22.3	22.8	22.7	23.2	23.7
12H	22.2	22.6	22.7	23.1	23.5	22.3	22.8	22.8	23.2	23.7
12H 4H	21.9	22.6	22.3	22.9	23.3	22.0	22.7	22.4	23.1	23.5
6H	22.1	22.6	22.5	23.0	23.4	22.2	22.7	22.6	23.1	23.6
8H	22.1	22.6	22.6	23.0	23.5	22.3	22.7	22.7	23.2	23.6

Variations with the observer position at spacings(CIE Pub.117):		
S = 1.0H	+ 0.7 / - 1.0	+ 0.7 / - 0.9
1.5H	+ 0.4 / - 0.4	+ 0.4 / - 0.5
2.0H	+ 1.5 / - 1.9	+ 1.5 / - 2.0

CIE Pub.117, 1884 lm Total Lamp Luminous Flux Corrected (8log(F/F0) = 2.2)
 Area: 0.032 m2

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	66	56	49	65	55	49	64	55	49	43
0.80	76	66	60	75	66	60	73	65	59	53
1.00	84	75	69	83	74	69	81	75	68	62
1.25	91	82	77	89	82	76	87	80	75	69
1.50	95	87	82	94	86	81	91	85	80	74
2.00	101	94	89	99	93	88	96	91	87	80
2.50	104	98	93	102	96	92	98	94	90	83
3.00	106	101	97	104	100	96	101	97	93	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	105	103	105	102	100	91
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

AAI Figure

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:

Flux out:1314 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators: DAMIN
 Test Date: 2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity: 65.0%
 Test Distance: 9.680m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:119.54V I:0.1285A P:15.059W PF:0.9807 Freq:60.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1883.7x1 lm		
NAME: DL254-8-35W-M-A5C5-HO	TYPE: 16W	WEIGHT:
SPEC.: 3500K	DIM.: 0.26	SERIAL No.: 1
MFR.: Lotus LED Lights	SUR.: 0.20	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	7639
L_0~180 (75) av	4065
L_0~180 (85) av	3517
L_90~270 (65) av	7528
L_90~270 (75) av	4081
L_90~270 (85) av	3042
L_45 (65) av	7591
L_45 (75) av	4084
L_45 (85) av	3345

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3℃
 Operators:DAMIN
 Test Date:2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity:65.0%
 Test Distance:9.680m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators: DAMIN
 Test Date: 2023-06-28

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.461
 Humidity: 65.0%
 Test Distance: 9.680m [K=1.0000]
 Remarks:

