



## Dimmer Compatibility List for Lotus LED Recessed Lights

LINE		GIMBALS				ULTIMATE 1/2"		ORIGINAL 1/2"		BUILDER GRADE			1" MODELS		SQUARE FLAT		REGRESSED		J-BOX	8"		
		LL2G & LRG2	LL3G & LRG3	LL4G & LRG4	LRG6	LL4R	LL6R	LY4RCS	LY6RCS	LB4R	LB6R	LB8R	LY41RCD	LY61RCD	LY4S	LY6S	LL4RRG & LL4SRG	LL6RRG & LL6SRG	LL4RBX	LY82RCD		
		5%				5%		20%		5%			20%		5%				20%			
BRAND	FAMILY	DIMMER MODEL	5W	7.5W	11.4W	15W	13.5W	17W	9W	12W	11W	14W	18W	12W	15W	11W	14W	14.5W	17/18W	11W	33W	
			W	RECOMMENDED NUMBER OF FIXTURES PER DIMMER AT 80% OF THE DIMMER CAPACITY																		
LUTRON	SKYLARK SKYLARK CONTOUR DIVA ARIADNI TOGGLER MAESTRO C-L  PANEL MODULE  Caseta	SCL-153P-XX STCL-153P-XX DVCL-153PH-XX AYCL-153P-XX YGCL-153H-XX MACL-153M-XX PHPM-PA with Grafik Eye QS Main Unit PHPM-WBX with 3-wire fluorescent control HW/LP-RPM-4A-120 Wireless	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-10	1-11	1-8	1-7	1-10	1-8	1-11	1-8	1-7	1-11	1-3	
	DIVA ARIADNI	DVCL-253PH-XX AYCL-253P-XX	250	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-17	1-18	1-14	1-11	1-17	1-13	1-18	1-14	1-11	1-18	1-6	
	Heavy Loads: use RRD-6CL to control PHPM-PA phase adaptive power module		up to 1600																			
	Electronic Low Voltage	DVELV-303P	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-17	1-18	1-14	1-11	1-17	1-13	1-18	1-14	1-11	1-18	1-6	
LEVITON	ILLUMATECH SURESLIDE DECORA	IPL06 6674 6618 6633	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-10	1-11	1-8	1-7	1-10	1-8	1-11	1-8	1-7	1-11	1-3	
		DSL06-1LZ	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-17	1-18	1-14	1-11	1-17	1-13	1-18	1-14	1-11	1-18	1-6	
COOPER	CORE DEVINE SLIDE DEVINE AL SERIES	DLC03P-W DAL06P SAL06P2	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-17	1-18	1-14	1-11	1-17	1-13	1-18	1-14	1-11	1-18	1-6	
Dimmer with Occupancy/Vacancy Sensor																						
Lutron	Maestro	MSCL-OP153M(H) MSCL-VP153M(H)	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-10	1-11	1-8	1-7	1-10	1-8	1-11	1-8	1-7	1-11	1-3	

EMAIL: [SUPPORT@LOTUSLEDLIGHTS.COM](mailto:SUPPORT@LOTUSLEDLIGHTS.COM) TEL. 1-844-24-LOTUS (1-844-245-6887)