**DESCRIPTION**

High Output High Efficiency Waterproof IP67 LED Tape Light 24V

APPLICATIONS


Cove and decorative lighting, path and contour marking
Outdoor, undercabinet and valance use
Suitable for installation in the storage area of a clothes closet

INSTALLATION INSTRUCTIONS

1. Remove transparent plastic cover of the double adhesive tape
2. Press LED strip firmly onto clean smooth surface that adsorbs heat, such as metal or glass. Start at one end and gradually move along surface, making sure the strip is smooth and not creased
3. Cut on trim marks that are printed on the back side

SEALING CUTS REQUIREMENTS

Do not use acidic or ketoxime-based adhesives when sealing cuts. Such adhesives can damage or corrode the strip surface. Use only alcohol-based, neutral-cure sealant. LED strips may be cut only at designated cut marks.

**WARNING**

LED tape gets hot. Mounting firmly and securely on smooth and thermo conductive surface such as metal or glass is critical for proper thermal management and long life. Not following these instructions voids the warranty

ORDERING GUIDE

2700K	LBL-24HO-27K-IP67-16FT
3000K	LBL-24HO-30K-IP67-16FT
4000K	LBL-24HO-40K-IP67-16FT



The package includes two extra end caps and a 10 mL tube of silicone glue

LBL-24HO-IP67-16FT**High Output LED Strip 24V 5.8W/ft CRI90+ Waterproof IP67**

Project: _____

Location: _____

Model # : _____

Qty: _____


Notes: _____

SPECIFICATION (tolerance +/- 10%)

Applications	Outdoor, Undercabinet, Cove, Valance, Decorative		
Power	5.8 W/ft / 19 W/m		
Color Temperature (K)	2700	3000	4000
Light output (lm/ft)	655	675	722
Efficiency (lm/W)	125	129	138
Maximum Length	16.4 ft / 5 meters		
Width	1/2" / 12 mm		
Power per Max Length	95 W		
Lumen per Max Length	11,800 lm		
Beam Angle	125°		
CRI	90 +		
Input	24V DC		
Dimmable	Yes		
LED Operation Type	Constant Voltage		
IP Grade	IP 67		
Approved Location	Outdoor / Wet Location / Clothes Closets		
Ambient Temperature	-4°F (-20°C) to +104°F (+40°C)		
Cuttable Increment	1 1/16"		
LEDs density	304 LEDs / meter		
Adhesive Tape Type	3M 300LSE with transparent backing		
Projected Life	70% Light Output at 50,000 Hours		
Certification	c UL us		
Warranty	3 year - when installed with a Lotus LED Lights driver The warranty is void if installed with an LED driver from another manufacturer		

ACCESSORIES

Connectors sold in bag of 5 pieces



[Tape to Wire connector model LBL-24HO-IP67-WireCap](#)

[Tape to Tape connector model LBL-24HO-IP67-TapeCap](#)

[90 degree connector model LBL-24HO-IP67-Corner](#)

[End Cap model LBL-24HO-IP67-EndCap](#)

RECOMMENDED DRIVERS

[KVG-24030-DWJ](#)

30W 5-in-1 Dimmable

[KVG-24060-DWJ](#)

60W 5-in-1 Dimmable

[KVG-24096-DWJ](#)

96W 5-in-1 Dimmable

[KVG-C24192-DWJ](#)

192W 5-in-1 Dimmable

[KVG-C24288-DWJ](#)

288W 5-in-1 Dimmable

[SDD-24060-DIM](#)

60W 2-in-1 driver + dimmer

[SDD-24096-DIM](#)

96W 2-in-1 driver + dimmer

**Lotus LED Lights USA**

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON